VITRŪV emboss

r

VITRŪV emboss

Vitruv Emboss is a new option in our line of hand applied concrete wall finishes. With Vitruv Emboss, our popular Carerra texture can be embossed with a select geometric pattern. The Carerra texture gives a concrete like appearance. A clear top coat is rolled on for extra durability creating a matte finish. Custom colors and patterns are available upon request. Contact your DFB sales representative for more information.



STANDARD PATTERNS







SLEET

FRACTAL

HEX

STANDARD COLORS



SPECIFICATIONS

Summary:	Durable decorative concrete system in a multi-part application incorporating a compatible base and finish coat.
Material Thickness:	1/16″
Max run without cross section :	15 feet
Emboss sizes:	1/8" & 3/16"
Acoustics:	ASTM C 423: NRC- 0.1 mounted on 5/8″ sheetrock
Environmental:	Vitruv contributes to LEED© v4, Compliance tested by Berkeley analytical for VOC Emission Test Certificate. CDPH compliant.
Custom Emboss:	Custom colors and patterns are available in the Carrera texture only. Please allow 8-10 business days per sample.
Lead time:	Vitruv is mixed in Long Island City, NY. Certain lead times may apply.
Installation:	Hand applied by DFB directly to level 4 finished wall.
Flammability:	System rated Class A; ASTM E84
Scrub Resistance:	15,500 cycles
Maintenance:	Clean with a mild liquid non-abrasive soap (e.g.: Dove, Ivory) diluted 75% with luke-warm water. Gently wipe surface with soft, clean, lint free cloth and carefully wipe off all soap residue. Denatured alcohol can be used in limited quantities to remove greasy or stubborn marks.

CUSTOM VITRUV

The DFB Vitruv Studio creates high-end finishes that work with your specific project colors. We can also match any Benjamin Moore color, color story, or swatch. Custom samples are developed upon request at the studio in Long Island City, NY. Please allow 8-10 business days.

