

# BAFFLE





Acoustics play an integral role in any environment. DFB has developed various sound absorbing techniques including our Baffle system, which offers both a decorative and highly functional solution to noise reduction. This application is suspended from the ceiling and can be installed in a multitude of patterns.

When wrapped in fabric, Panel Tex Baffles offer a 1.0 Noise Reduction Coefficient (NRC) rating. DFB recommends Camira Blazer fabrics for this application, as well as our Quiet-Core™ substrate, which meets the following standards; ASTM E84, ASTM 5166, & ASTM D6196. Explore the most popular 50 colors from the latest fabric line.












Dartmouth




Stanford




Barnard




Holyoke




Vassar



Woodcroft




Marymount




Abertay



Eynesbury




Vassar




Montcrest




Barlborough



Scottsdale



Sheffield




Aston



Manchester




Knightsbridge



Newcastle




Oxford




Glenalmond


Always request physical fabric samples prior to ordering to ensure color accuracy.




Latymer




Tyndale




Cardiff



Glasgow



Edinburgh




Ulster




Camphill




Bryanson



Newport



Dunhurst



Wesley



St. Andrews



Fairfield




Goldsmith




Edgehill




Handcross



Oriel



Wellington




Magdalene




Silverdale

Always request physical fabric samples prior to ordering to ensure color accuracy.






Plymouth



Surrey



Aberlour



Trevelyan




Bromsgrove




Kingsmead




Silcouts



Winchester



Hull



Napier



## Specifications

Name: Panel-Tex Baffle

Manufacturer: DFB Sales, 21-07 Borden Avenue, Long Island City, NY 11101

Substrate/Content: Quiet-Core Formaldehyde free fiberglass

Environmental: Rapidly renewable and compostable.

Panel Max Height: 24"

Panel Thickness: 2"

Maximum Length: 96"

Hardware: Includes panels + ceiling mounting system

Maintenance: Vacuum occasionally

Lead Time: 4-6 weeks

Custom: Available upon request.

Acoustics: ASTM C 423: NRC-1.0 SAA 1.0

Recommended Fabrics: Camira Blazer

Flammability: California Technical Bulletin 117-2013; NFPA 260 + UFAC Class 1

## Detail Drawing

