





Plank Panels

Fabric: Ultrafabrics Brisa®

Color: Quicksilver





PLANK PANELS

These fabric wrapped, acoustical panels are distinguished by their rounded edges, and can be configured using our standard 5" and 10" wide panels.

As part of DFB's prefabricated Panel-Tex™ system, Plank is made to order in Long Island City, NY.

Substrate(s)	Quiet-Core™ (Acoustical)
Panel Widths	5" & 10". Custom sizes available
Maximum Length	120"
Mounting Options	Quick grab formula and concealed nails
Lead Time	4 weeks
Acoustics	0.8 NRC
Fire Rating	In accordance with ASTM E84, fabric wrapped panels achieve a Class A rating, passing NFPA 701
Environmental	Rapidly renewable and compostable









As the first breathable performance fabric in its class, Brisa® is designed with beauty, functionality, and durability in mind. Unlike standard leather hides, this green alternative to leather, does not have size limitations for upholstery, and delivers the added benefit of sound absorption.

Pair Brisa® with DFB's prefabricated Panel-Tex™ panels, for a sharp and sophisticated look. Brisa® can be wrapped around square, beveled, and rounded edge, Plank panels.

Composition	100% Polycarbonate Polyurethane Surface. 65% Polyester, 35% Rayon Backing
Weight	Approx. 9.3 oz. Per Square Yard
Thickness	Approx. 1.0 Millimeters
Width	54 inches
Abrasion	ASTM D4157 / 300,000 Double Rubs BS 2543 / 160,000 Rubs
Sound Absorption	ASTM C423
Light Fastness	AATCC 16.3, 200 Hours, Grade 4-5
Noise Reduction	NRC rating of 0.80 when paired with our Quiet-Core™ substrate
Fire Classification	F/R Rating: ASTM E84 (Adhered) - Class ACA TB 117-2013, FMVSS 302 & 95/28 Annex IV, NFPA 260 - Class 1, UFAC - Class 1, ASTM E84 (Unadhered), BS 5852 PT 0, 1 & 5 (Crib 5), BS 5867 Part 2 Type B, BS 7175, California Technical Bulletin 133, FAR Specifications, IMO A.652 (16), NFPA 701































